

## Technical Data Sheet [TDS]

### AAT-275 Ultra Premium Adhesive

AAT-275 Ultra Premium Adhesive is a Go2 Adhesive specifically formulated for the heaviest commercial applications. AAT's Go2 Adhesive formulas have been formulated to ensure adhesive performance under the very demanding conditions commonly found in today's fast paced construction. This ultra-strong, low VOC adhesive is excellent for woven carpets, those with stiff unitary backings, and attached cushion backings. AAT-275 Ultra Premium Adhesive is THE professional's choice for Double-Glue and pattern matching applications. This formula has an extended working time and superior re-tack engineered to maximize installer efficiency. AAT-275 is backed by a Limited-Lifetime Warranty (for installations after Feb. 1, 2003).

AAT-275 Ultra Premium Adhesive can be used for the following carpet backings and floor coverings:

- Direct-Glue: woven polypropylene (ActionBac®, hot melt, etc.) latex unitary, polyurethane foam-backed (Enhancer® I,II,III,IV, BioCel™ and Durafoam), rubber backs, woven, axminster, needlepunch, and jute
- Double-Glue: 275 is recommended for double-glue "carpet to pad" applications with specific carpet backings approved by AAT for this application. This adhesive can also be used to adhere approved double-glue carpet cushions.
- Although this adhesive is formulated for carpet installations, because of its non-staining characteristics, it can be used to install felt backed sheet vinyl.



**Note:** This adhesive is not recommended for vinyl backed (PVC) sheet goods or carpets with urethane unitary or vinyl (PVC) backings.

AAT-275 may contribute to the LEED certification of projects in the following categories:

- IEQ Credit 4.1—Low Emitting Materials – Adhesives & Sealants
- IEQ Credit 4.3—Low Emitting Materials – Flooring Systems
- IEQ Credit 5—Regional Materials

#### Sub-floor and Site Conditions:

Recommended Sub-floors • Concrete above, on or below grade • APA rated plywood underlayment • Properly prepared gypsum cement

Sub-floors on and below grade must be protected from ground moisture with a functioning and intact Class A vapor retarder that conforms to the requirements of the most current version of ASTM E-1745. This vapor retarder must be directly beneath, and in contact with, the slab. Concrete sub-floors must be properly prepared according to the practices detailed in the latest standard, ASTM F-710. Gypsum sub-floors must meet the requirements of the most current version of ASTM F-2419. All curing agents [topical and admix], adhesives, paints, varnishes, oils, waxes, dust, dirt and any other bond inhibiting substances must be removed. The removal of bond inhibiting substances must be by mechanical means: sanding, shot or bead blasting. AAT-275 cannot be used if adhesive removers, solvent or chemical cleaners have been used.

The maximum moisture emission rate of the sub-floor cannot exceed 8lbs/1000 sq.ft./24 hours [ASTM F-1869], with a pH of 7.0- 9.0 [ASTM F-710], and a maximum *in situ* RH of 90% [ASTM F-2170]. Prior to the application of AAT-275, sub-floors must be tested in strict accordance to the most recent versions of ASTM F-1869 and F-2170. Both testing protocols must be performed in order to provide the most accurate view of the sub-floor's condition. Sub-floors of lightweight concrete must be tested in strict accordance to the most recent version of ASTM F-2170. The placement of calcium chloride kits and humidity probes must follow the ASTM standards for proper locations and the correct quantity of test sites. These and other tests may be performed by AAT in the event of a warranty claim.

All sub-floors must be flat and structurally sound. Smooth or glazed surfaces must be abraded. Repair all joints and cracks with latex-based portland cement underlayments. Never sand existing resilient flooring that could contain asbestos. Follow all Federal, State and Local regulations relating to the removal of in-place, asbestos containing material. Very porous sub-floors must be primed with AAT-570 Primer.

**Note:** Strip or plank wood flooring, particleboard and OSB sub-floors should be covered with an approved underlayment (minimum thickness of ¼"). AAT-275 cannot be used if adhesive removers, solvent or chemical cleaners have been used. Before beginning installations with backing systems or over sub-floors not listed contact AAT's Technical Services for recommendations. AAT Technical Services can be reached at 1(800)228-4583 or by email at [techservice@aatglue.com](mailto:techservice@aatglue.com). It is the sole responsibility of the applicator of this product to determine the suitability and compatibility of this product for their intended use. *If the provided preparation and application instructions are not followed, DO NOT USE AAT-275.*

#### **Installation Recommendations:**

Typical trowels and approximate coverage: (depth x width x spacing)

**Woven polypropylene, woven, axminster:** 1/8" x 1/8" x 1/8" U notch, 100 sq. ft. /gal.

**Attached cushions:** 3/32" x 3/32" x 3/32" V notch, 125 sq. ft. /gal.

**Unitary and Double-Glue (carpet to cushion):** 1/8" x 1/8" x 1/16" U notch, 50 sq. ft./gal.

**Felt backed Sheet Vinyl:** 1/16" x 1/16" x 1/16" □ notch, 150 sq. ft./gal.

The building should be completely enclosed. All outside doors and windows should be properly installed with latching mechanisms in place. Adequate ventilation should be available. The HVAC system for the building should be operational and provide a consistent temperature of 65-85°F (air and sub-floor) and humidity levels should be between 40-65% for a minimum of 72 hours prior to the installation. These conditions must be maintained to ensure the long term success and performance of the installation.

1. Flooring and adhesive should be acclimated to the job site conditions for a minimum of 24 hours prior to the installation.
2. Be familiar with the recommendations and any special instructions from the flooring manufacturer before beginning the installation. Follow the flooring manufacturer's specific recommendations regarding sub-floors and seam sealing.
3. Refer to the information above for specific information regarding sub-floor preparation and site conditions.
4. Spread the adhesive with the appropriate trowel as defined above. Allow the appropriate dwell or open time. Lay the carpet into the adhesive as to minimize bubbles and wrinkles.
5. Roll the flooring with a three-section roller [Carpet - 75lb. for direct glue and 35lb. double-glue; Sheet vinyl – 100lb.] to ensure adequate transfer. Wet adhesive transfer to the flooring must be 100%.
6. Roll the flooring "north to south" and "east to west" from center to edge forcing out air pockets and eliminating wrinkles.

#### **Specific Technical Data:**

- Base: SBR-resin emulsion
- Color: yellow-tan
- Flammability: Non-flammable
- Shelf Life: One year from date of manufacture in an unopened container
- Freeze-Thaw Stable: If frozen, allow to thaw at room temperature. Do NOT stir or agitate while frozen. Stability and spread-ability can be reduced if frozen. For best results do not allow to freeze.
- Clean-up: Remove wet adhesive with damp cloth (plain water). Use AAT-197 Adhesive Remover for dried adhesive.
- VOCs: 0 g/l (Calculated per Ca. Rule 1168); Solvent Free
- Not recommended for exterior installations.

**NOTE:** We recommend installers follow the guidelines set forth in the latest version of the CRI's *Carpet Installation Standard - 104*. Before placing the carpet, the adhesive must be allowed an open or dwell time appropriate for the carpet backing, jobsite and sub-floor conditions. It is extremely important to maintain recommended notch depth, width and spacing. The proper notch depth is that which will produce adhesive ridges that affect a 100% transfer to both the substrate and the carpet backing to include the inner recesses of the texture of the back.



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

### 1 Identification

- **Product identifier**
- **Trade name: AAT-275**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Advanced Adhesive Technologies  
424 South Spencer Street  
Dalton, GA 30721  
+1 (800) 228-4583
- **Emergency telephone number:**  
CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 2      H351 Suspected of causing cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Warning
- **Hazard-determining components of labeling:**  
1,2-benzisothiazol-3(2H)-one  
ethyl acrylate
- **Hazard statements**  
May cause an allergic skin reaction.  
Suspected of causing cancer.
- **Precautionary statements**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin: Wash with plenty of water.  
If exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 1)

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 0

Fire = 0

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1332-58-7	Kaolin	43.29%
471-34-1	calcium carbonate	3.11%
140-88-5	ethyl acrylate	0.824%
2634-33-5	1,2-benzisothiazol-3(2H)-one	0.078%

### 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 2)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	140 mg/m <sup>3</sup>
471-34-1	calcium carbonate	45 mg/m <sup>3</sup>
140-88-5	ethyl acrylate	8.3 ppm
57-13-6	urea	30 mg/m <sup>3</sup>
141-43-5	2-aminoethanol	6 ppm

- **PAC-2:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1,500 mg/m <sup>3</sup>
471-34-1	calcium carbonate	210 mg/m <sup>3</sup>
140-88-5	ethyl acrylate	36 ppm
57-13-6	urea	280 mg/m <sup>3</sup>
141-43-5	2-aminoethanol	170 ppm

- **PAC-3:**

64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	8,900 mg/m <sup>3</sup>
471-34-1	calcium carbonate	1,300 mg/m <sup>3</sup>
140-88-5	ethyl acrylate	240 ppm
57-13-6	urea	1,700 mg/m <sup>3</sup>
141-43-5	2-aminoethanol	1,000 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 3)

- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

At this time, the other constituents have no known exposure limits.

### 1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 2* mg/m <sup>3</sup> E; as respirable fraction

### 471-34-1 calcium carbonate

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	TLV withdrawn

### 140-88-5 ethyl acrylate

PEL	Long-term value: 100 mg/m <sup>3</sup> , 25 ppm Skin
REL	See Pocket Guide App. A
TLV	Short-term value: 61 mg/m <sup>3</sup> , 15 ppm Long-term value: 20 mg/m <sup>3</sup> , 5 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

- **Breathing equipment:** Not required.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.

- **Vapor pressure:** Not determined.

- **Density:** Not determined.

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

**Water:** Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 5)

- **Solvent content:**
  - Organic solvents:** 0.4 %
  - Water:** 16.1 %
  - VOC content:** 0.35 %
  - 3.5 g/l / 0.03 lb/gl
- **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 471-34-1 calcium carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

### 140-88-5 ethyl acrylate

Oral	LD50	800 mg/kg (rat)
Dermal	LD50	1,834 mg/kg (rabbit)
Inhalative	LC50/4 h	2,180 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

140-88-5	ethyl acrylate	2B
----------	----------------	----

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 6)

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- |  |                 |
|--|-----------------|
| · <b>UN-Number</b>   |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>UN proper shipping name</b>   |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>Transport hazard class(es)</b>  |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  |                 |
| · <b>Class</b>   | not regulated   |
| · <b>Packing group</b>   |                 |
| · <b>DOT, IMDG, IATA</b>   | not regulated   |
| · <b>Environmental hazards:</b>  | Not applicable. |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>  | not regulated   |

US

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: AAT-275

(Contd. of page 7)

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **TSCA (Toxic Substances Control Act):**

1332-58-7	Kaolin
68131-77-1	Petroleum Hydrocarbon Resin
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
471-34-1	calcium carbonate
140-88-5	ethyl acrylate
57-13-6	urea
141-43-5	2-aminoethanol
68610-51-5	phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene
2634-33-5	1,2-benzisothiazol-3(2H)-one
7732-18-5	water, distilled, conductivity or of similar purity

· **Proposition 65**

· **Chemicals known to cause cancer:**

140-88-5	ethyl acrylate
----------	----------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.
------------------------------------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.
------------------------------------

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.
------------------------------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

57-13-6	urea	II
---------	------	----

· **TLV (Threshold Limit Value established by ACGIH)**

1332-58-7	Kaolin	A4
140-88-5	ethyl acrylate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

140-88-5	ethyl acrylate
----------	----------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

1,2-benzisothiazol-3(2H)-one  
ethyl acrylate

· **Hazard statements**

May cause an allergic skin reaction.

(Contd. on page 9)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/18/2018

Reviewed on 02/12/2018

Trade name: **AAT-275**

(Contd. of page 8)

Suspected of causing cancer.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Technical Department

- **Contact:** Technical Director

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2